

MATERIAL SAFETY DATA SHEET
Essentially Similar to U.S. Department of Labor Form OSHA
Revised 03/24/05
HMIS Health-1 Flammability-3 Reactivity-0
SECTION I-Product Information

Manufacturer: A.V.W. Inc.
24 Hour Emergency Phone Number: 800-424-9300
Product Name: Get Off Ink & Adhesive Remover

SECTION II

Hazardous Ingredients

2-Butoxyethanol	CAS# 111-76.-2	TWA 100	% 20-40
Isopropanol	CAS# 6763-0	TWA 400	20-30
Mineral Spirit	CAS# 8052-41-3	TWA 200	20-30
Propane	CAS# 74-98-6	TWA1000	18-23
Butane	CAS# 106-97-8	TWA 800	12-17

SECTION III

Physical Data

Boiling Point: 188 F
 Specific Gravity (H₂O=1)=0.86
 Solubility in water: .0%
 Appearance: Colorless liquid with penetrating cellosolve odor

SECTION IV

Fire and Explosion Hazard Data

Flash Point: 98F Extremely Flammable Level 3 Aerosol
 Extinguishing media: Water, CO₂, and foam, dry chemical
 Special fire Fighting Procedures: Do not expose containers to temps above 120° F.
 Unusual fire and Explosion: Forms flammable vapor-air mixtures. Lower temperatures increase the difficulty of getting it to ignite.

SECTION V

Health Hazard Data

Time weighted average (TWA): 100 ppm based in the raw material.
 Carcinogen: NO
 Acute chronic health effects: Excessive exposure may cause irritation to upper respiratory tract. Excessive exposure may cause carboxyhemoglobinemia, they're by impairing the blood's ability to transport oxygen.
 Primary Routes of Entry: X Inhalation X Skin X Ingestion
 Effects of Overexposure: Eyes-May causes pain, moderate eye irritation and slight corneal injury. Vapors may irritate eyes.
 Skin: May cause irritation. Repeated contact may cause drying or flaking of skin.
 Inhalation: In confined or poorly ventilated areas, vapors can readily accumulated and cause unconsciousness and death.
 Ingestion: May be harmful.
 Emergency First Aid Procedures: Eyes- Flush with water 15 minutes. Get medical attention if irritant persist.
 Skin: Wash with soap and water.
 Ingestion: Do not induce vomiting. Get medical attention immediately.
 Inhalation: Move to fresh air. Get medical attention

SECTION VI

Reactivity Data

Stability: stable X
 Conditions to Avoid: Hydrolysis producing small amounts of hydrochloric acid possible with gross water contamination.
 Avoid open flames, welding arcs, or other high temperature sources, which induce thermal decomposition.
 Incompatibility: Strong Oxidizers; caustics, chemically active metals such as aluminum, magnesium & sodium.

SECTION VII

Spill or Leak Procedures

Steps to take in case material is released or spilled: Use absorbent material and trash receptacle. Waste disposal method Federal and Local regulations.

SECTION VIII

Special Protection Information

Respiratory Protection: Adequate ventilation.

Gloves (type): Chemical resistant

Eye protection: Glasses if required

Other Protective Equipment: None

SECTION IX

Special Precautions

Precautions to be taken in handling and storing read and follow all label directions. Do not store containers at temperatures above 120°F.