

MATERIAL SAFETY DATA SHEET
Essentially Similar to U.S. Department of Labor Form OSHA
Revised: 03/24/05
HMIS Health-1 Flammability-3 Reactivity 0
SECTION I-Product Information

Manufacturer: A.V.W. Inc.**24 Hour Emergency Phone Number: 800-424-9300****Product Name: Blow Off Rubber Rejuvenator****SECTION II-Hazardous Ingredients**

Xylene	CAS#	95-47-6	TWA	100	% 25-30
Methanol	CAS#	67-56-1	TWA	200	0.1- 3
Mineral Spirit	CAS#	8052-41-3	TWA	200	5-10
Acetone	CAS#	67-64-1	TWA	1000	1-5
Isopropanol	CAS#	6763-0	TWA	400	25-30
Propane	CAS#	74-98-6	TWA	1000	18-23
Butane	CAS#	106-97-8	TWA	800	12-17

SECTION III-Physical Data

Boiling Point:	188 F
Specific Gravity	(H2O=1)=.86
Solubility in Water:	.0%
Appearance:	Colorless liquid with penetrating ether like odor.

SECTION IV-Fire and Explosion Hazard Data

Flash Point:	98 F Extremely Flammable Level 3 Aerosol
Extinguishing Media:	Water, CO2, Foam, Dry Chemical
Special Fire Fighting Procedures:	Do not expose containers to temperatures above 120 F.
Unusual Fire and Explosion:	Forms flammable vapor air mixtures. Lower temperatures increase the difficulty of getting it to ignite.

SECTION V-Health Hazard and First Aid

Time Weighted Average (TWA):	100 ppm based in the raw material.		
Carcinogen:	No		
Acute Chronic Health Effects:	Excessive exposure may cause irritation to upper respiratory tract. Excessive exposure may cause carboxyhemoglobinemia, thereby impairing the bloods ability to transport oxygen.		
Primary Routes of Entry:	X Inhalation	X Skin	X Ingestion
Effects of Overexposure:	Eyes- May cause pain, moderate eye irritation and slight corneal injury. Vapors may irritate eyes.		
	Skin- May cause irritation. Repeated contact may cause drying or flaking of the skin.		
	Inhalation- In confined or poorly ventilated areas, vapors can readily accumulate and cause unconsciousness and death.		
	Ingestion- May be harmful.		
First Aid:	Eyes- Flush with water for 15 minutes. If		

irritation persists get medical attention.

Skin- Wash with soap and water.

Inhalation- Move to fresh air. Get medical

attention.

Ingestion- Do not induce vomiting. Get medical

attention immediately.

SECTION VI-Reactivity Data

Stability:

Stable X

Conditions to Avoid:

Hydrolysis producing small amounts of hydrochloric acid possible with gross water contamination. Avoid open flames, welding arcs, or other high temperature sources, which induce thermal decomposition.

Incompatibility:

Strong oxidizers; caustics, chemically active metals such as aluminum, magnesium and sodium.

SECTION VII-Spill or Leak Procedures

Steps to take in case material is spilled or released: Use absorbent material and trash receptacle. Waste disposal method Federal and Local regulations.

SECTION VIII-Special Protection Information

Respiratory Protection:

Adequate ventilation

Gloves (type):

Chemical resistant

Eye Protection:

Glasses (if required)

Other Protective Equipment:

None

SECTION IX-Special Precautions

Precautions to be taken in handling and storing: Read and follow all label directions. Do not store containers at temperatures above 120 F.