

MATERIAL SAFETY DATA SHEET
Essentially Similar to U.S. Department of Labor Form OSHA
Revised 03/24/05
HMIS Health-1 Flammability-3 Reactivity 0
SECTION I-Product Information

Manufacturer Name: A.V.W. Inc.
24 Hour Emergency Phone Number: 800-424-9300
Product Name: Get Off Screen Opener

SECTION II
Hazardous Ingredients

Ingredient	CAS#	Concentration	TWA	%
Xilene	95-47-6		100	5-10
Ciclhexanone	108-94-1		25	15-25
2 Butoxiethanol	111-76-2		25	1- 5
Acetone	67-64-1		1000	4-8
Isopropanol	6763-0		400	4-8
Mineral Spirit	8052-41-3		200	35-45
Propane	74-98-6		1000	5-15
Butane	106-97-8		800	5-15

SECTION III
Physical Data

Boiling Point: 188 F
Specific Gravity(H₂O=1)=0.80
Solubility in water: .0 %
Appearance: Colorless liquid with penetrating ether-like odor

SECTION IV
Fire and Explosion Hazard

Flash Point: 104F Extremely Flammable
Extinguishing media: Water, CO₂, Foam, Dry chemical
Special fire Fighting Procedures: Do not expose containers to temps. above 120 F.
Unusual fire and Explosion: Forms flammable vapor-air mixtures. Lowers temperatures increase the difficulty of getting it to ignite

SECTION V
Health Hazard Data

Time weighted average (TWA): 25PPM based in the raw material
Carcinogen: No
Acute Chronic Health effects: Excessive exposure may cause irritation to upper respiratory tract. Excessive exposure may cause carboxyhemoglobinemia they're by impairing the blood's ability to transport oxygen
Primary Routes of Entry: X Inhalation X Skin X Ingestion
Effects of Overexposure: Eyes- May cause pain, moderate eye irritation and slight cornea injury. Vapors may irritate eyes, Skin: May cause irritation. Repeated contact may cause drying or flaking of skin.
Inhalation: In confined or poorly ventilated areas, vapors can readily accumulated and cause unconsciousness and death.
Ingestion: May be harmful
Emergency First Aid Procedures: Eyes- Flush with water 15 minutes. Get medical attention if irritant persist.
Skin: Wash with soap and water.
Ingestion: Do not induce vomiting. Get medical attention immediately.
Inhalation: Move to fresh air. Get medical attention.

SECTION VI
Reactivity Data

Stability: stable X
Conditions to Avoid: Hydrolysis producing small amounts of hydrochloric acid possible with gross water contamination. Avoid open flames, welding arcs, or other high temperature sources, which induce thermal decomposition.
Incompatibility: Strong Oxidizers; caustics, chemically active metals such as aluminum, magnesium & sodium.

SECTION VII

Spill or Leak Procedures

Steps to take in case material is released or spilled: Use absorbent material and trash receptacle. Waste disposal method Federal and Local regulations.

SECTION VIII

Special Protection Information

Respiratory Protection: Adequate ventilation.

Gloves (type): Chemical resistant

Eye protection: Glasses if required

Other Protective Equipment: Technician Use only

SECTION IX

Special Precautions

Precautions to be taken in handling and storing read and follow all label directions. Do not store containers at temperatures above 120°F.